

JCB



Helac PowerTilt Selection Guide

Effective February 1, 2008/Rev

Helac PowerTilt can be provided for standard duty* and heavy duty** applications for many JCB machines as outlined in the charts below. Note some models require non-OEM-mounting pins.

Compact Excavators

JCB Model	PowerTilt Model		OEM Pins	Pin Kit List Price USD
	Standard Duty*	Heavy Duty**		
8027Z/8032Z	N/A	PT-06	No	\$220.00
804 SUPER	N/A	PT-06	No	\$220.00
8052	PT-6W	PT-07	No	\$240.00
8060	PT-07	PT-08	No	\$240.00

Full-Size Excavators

JCB Model	PowerTilt Model		OEM Pins	Pin Kit List Price USD
	Standard Duty*	Heavy Duty**		
8080 ZTS	N/A	PT-08	No	\$240.00
JS 130	PT-09	PT-10	Yes-ST No-HD	\$520.00
JS 160L/NL	N/A	PT-10	Yes	N/A
JS 220	PT-11	PT-12	Yes	N/A
JS 260	N/A	PT-12	Yes	N/A
JS 330	PT-12	N/A	Yes	N/A

Backhoe/Loaders

JCB Model	PowerTilt Model		OEM Pins	Pin Kit List Price USD
	Standard Duty*	Heavy Duty**		
3CX	PT-07	PT-08	No	\$240.00
4CX	PT-07	PT-08	No	\$240.00
Heavy 4CX	N/A	PT-08	No	\$240.00

*Standard Duty: General excavating, ditch cleaning, work site grading, sloping and landscaping.

**Heavy Duty: Excavating in hard digging conditions and occasional use of hydraulic breakers, rippers, vibratory compactors and demolition work.



JCB

Helac PowerGrip Selection Guide

Effective February 1, 2008/Rev

Helac PowerGrip buckets are provided with lugging that is compatible to the OEM mounting dimensions and pins. Bucket teeth are standard*.

Excavators

JCB Model	PowerGrip Model	Bucket Style	Bucket Size
8052	PG-06-5T-24"	Trenching	4.5 ft3
8060 8080 ZTS	PG06-24"	Trenching	7.5 ft3
	PG06-30"	Trenching	9.4 ft3
	PG07-24"	Trenching	7.5 ft3
	PG07-30"	Trenching	9.4 ft3
	PG07-36"	Trenching	11.3 ft3
JS 130	PG07-24"	Trenching	0.5 yard
	PG07-30"	Trenching	0.625 yard
	PG07-36"	Trenching	0.75 yard
	PG07-48"	Trenching	1.0 yard
JS 160L/NL	PG07-48"	Ditching	0.875 yard
	PG07-60"	Ditching	1.3 yard
JS 160L/NL	PG08-30"	Trenching	.76 yard
	PG08-36"	Trenching	.95 yard
	PG08-42"	Trenching	1.14 yard
	PG08-48"	Trenching	1.31 yard

Backhoe/Loaders

JCB Model	PowerGrip Model	Bucket Style	Bucket Size
3CX 4CX	PG06-24"	Trenching	7.5 ft3
	PG06-30"	Trenching	9.4 ft3
Heavy 4CX	PG07-24"	Trenching	7.5 ft3
	PG07-30"	Trenching	9.4 ft3
	PG07-36"	Trenching	11.3 ft3

*Standard bucket tooth options available are compatible with CAT, ESCO, Hensley and John Deere. Special tooth options are available for an additional fee.

Trenching bucket for 12 ton and larger excavators have the option of CAT or ESCO side cutter bolt hole patterns.

Important Notice

This document is general in nature and does not obligate Helac Corporation to any specific applications. The dealer and customer are solely responsible for the verification of attachment sizing when adding tools and attachments to a specific carrier/machine.