



## Helac Attachments Selection Guide

Effective February 1, 2008/Rev



### PowerTilt Swing Attachment

Helac PowerTilt can be provided for standard duty\* and heavy duty\*\* applications for many Takeuchi machines as outlined in the chart below. Note some models require non-OEM-mounting pins.

Takeuchi Model	PowerTilt Model		OEM Pins	Pin Kit List Price USD
	Standard Duty*	Heavy Duty**		
TB125	N/A	PT-06	No	\$220.00
TB135	N/A	PT-06	Yes	N/A
TB138 FR	N/A	PT-06	Yes	N/A
TB145	PT-6W	PT-07	No	\$280.00
TB153 FR	N/A	PT-07	No	\$280.00
TB175	PT-07	PT-08	Yes	N/A
TB180 FR	PT-07	PT-08	Yes	N/A
TB1140	PT-09	N/A	Yes	N/A

\*Standard Duty: General excavating, ditch cleaning, work site grading, sloping and landscaping.

\*\*Heavy Duty: Excavating in hard digging conditions and occasional use of hydraulic breakers, rippers, vibratory compactors and demolition work.

### PowerGrip Multi-Purpose Bucket

Helac PowerGrip buckets are provided with lugging that is compatible to the OEM mounting dimensions and pins. Bucket teeth are standard\*.

Takeuchi Model	PowerGrip Model	Bucket Style	Bucket Size
TB145 TB153 FR	PG06-5T-24"	Trenching	4.5 ft3
TB175	PG06-24"	Trenching	7.5 ft3
	PG06-30"	Trenching	9.4 ft3
	PG07-24"	Trenching	7.5 ft3
	PG07-30"	Trenching	9.4 ft3
	PG07-36"	Trenching	11.3 ft3
TB1140	PG07-24"	Trenching	0.50 yard
	PG07-30"	Trenching	0.625 yard
	PG07-36"	Trenching	0.75 yard
	PG07-48"	Trenching	1.0 yard

\*Standard bucket tooth options available are compatible with CAT, ESCO, Hensley and John Deere. Special tooth options are available for an additional fee.

Trenching bucket for 12 ton and larger excavators have the option of CAT or ESCO side cutter bolt hole patterns.

#### Important Notice

This document is general in nature and does not obligate Helac Corporation to any specific applications. The dealer and customer are solely responsible for the verification of attachment sizing when adding tools and attachments to a specific carrier/machine.